



CAPACITIES & SPECIFICATIONS

Model	Nominal capacity (kW)	HP	Heat transfer area (M ²)	FAN		Fin Pitch (mm)	Fin Length (mm)	Connect dia (mm)		Overall (mm)	Pattern
				Qty	OD (mm)			Inlet	Outlet		
WFN-2	0.6	1/4	2	1	200	2.35	270	3/8	3/8	320x100x235	2 x 4
WFN-3.4	1	3/8	3.4	1	200	2.1	270	3/8	3/8	320x100x235	3 x 4
WFN-4.4	1.3	1/2	4.4	1	250	2.4	325	3/8	3/8	370x100x285	3 x 5
WFN-5.4	1.6	3/4	5.4	1	300	2.85	392	3/8	3/8	440x100x330	3 x 6
WFN-7.0	2	1	7	1	300	2.9	390	Φ12	Φ12	440x135x330	4 x 6
WFN-8.4	2.3	1.2	8.4	1	350	2.8	455	Φ16	Φ12	500x130x430	3 x 8
WFN-11.5	3.5	1.5	11.5	1	350	2.6	430	Φ16	Φ12	480x180x430	4 x 8
WFN-15	4.4	2	15	1	350	2.55	530	Φ16	Φ12	550x180x480	4 x 9
WFN-18	5.2	2 1/2	18	1	400	2.55	530	Φ19	Φ16	590x180x530	4 x 10
WFN-22	6.4	3	22	1	400	2.6	660	Φ19	Φ16	590x180x530	5 x 10
WFN-25	8.1	3.5	25	1	400	3	790	Φ16	Φ12	750x180x680	4 x 11
WFN-21	6.1	3	21	2	300	1.95	840	Φ19	Φ16	840x180x430	3 x 8
WFN-28	8.2	3.5	28	2	350	2.1	840	Φ19	Φ16	900x180x430	4 x 8
WFN-33	11.2	4	33	2	350	2.45	950	Φ19	Φ16	900x200x480	5 x 9
WFN-36	12.6	5	36	2	400	2.5	950	Φ22	Φ19	1015x180x580	4 x 11
WFN-43	14.8	6	43	2	400	2.5	1172	Φ22	Φ19	1015x180x680	4 x 13
WFN-48	17.5	6.5	48	2	400	2.5	1172	Φ25	Φ22	1250x200x630	4 x 12
WFN-55	19.2	7.5	55	2	400	2.59	1172	Φ22	Φ19	1250x200x730	4 x 14
WFN-70	20.5	10	70	4	300	2.3	1172	Φ22	Φ19	1250x200x830	4 x 16
WFN-80	24.4	12	80	4	400	2.3	1172	Φ25	Φ22	1250x200x930	4 x 18
WFN-100	29.6	13	100	4	400	2.2	1172	Φ25	Φ22	1250x200x1130	4 x 22
WFN-130	38.2	15	130	4	400	2.1	1172	Φ25	Φ22	1250x200x1380	4 x 27
WFN-150	47.2	20	150	4	400	2.3	1240	Φ25	Φ22	1250x250x1330	5 x 26
WFN-180	58	25	180	4	400	2.3	1240	Φ25	Φ22	1250x270x1330	6 x 26
WFN-210	69.5	30	210	6	400	2.4	1650	Φ32	Φ25	1720x255x1230	6 x 24